



Neon Specification

6 x 6 mm Flex LED



【Features】

- Light source: High luminous efficiency, LM80 proved.
- Process & Material: High light transmittance, environmental silicone material, IP65.
- Optical Design: Unique optical light distribution structure design, uniform lighting surface and no shadow.
- Appearance Design: Compared with the traditional neon tube or PVC guardrail tube, the silicone material has good flexibility, the simple and stylish appearance, which is exquisite and unique.
- Product Certification: UL、CE、ROHS、CB、UKCA ;
- Environmental Features: Resistance to saline solutions, acids & alkali, corrosive gases and UV.
- Working/Storage Temperature: Ta:-25~55°C /0°C ~ 60°C.
- Application:Furniture supporting lighting,Outdoor/indoor lighting,Indoor general lighting.
- White with 3 years warranty or working life =36000H,whichever comes first.




【Basic Parameters】

Model	CCT/colors	CRI	Input voltage (V)	Rated current (A/ft)	Rated power (W/ft)	MAX power (W/ft)	Lumens (LM/m)	Length	Remark
NTT0606-9XX12CSN050CCXXX	2300K	>90	12	0.6 (0.18A/ft)	7.2 (2.19W/ft)	8.3 (2.53W/ft)	400 (122LM/ft)	5000mm (16.4ft)	3LED/10.87mm
	2700K						450 (137LM/ft)		
	3000K								
	4400K								
NTT0606-9XX24CSN050CCXXX	2300K	>90	24	0.3 (0.09A/ft)	7.2 (2.19W/ft)	8.3 (2.53W/ft)	400 (122LM/ft)	5000mm (16.4ft)	7LED/25mm
	2700K						450 (137LM/ft)		
	3000K								
	4400K								

Note :

- 1、 The above data is the testing result of 1M standard product;
- 2、 The lumens of output data can be vary up to ±10%;
- 3、 The above parameters are all typical values.


【Light Distribution】



Light distribution

Note: The above data is based on 24V monochrome 4000K color temperature. If you need other models of IES files, please download the corresponding models from the IES database.

Flux out:341.5 lm




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.










Effective average illuminance

【Product Mechanical Parameters】



• IP65 Glued cap-top outlet



【Accessory Information】

Name	Description	Image	Sectional size	Ordering code	Quantity case (PCS)	Net weight (kg)	Perbox net weight (kg)	Gross weight (kg)	Packing (mm)	Remark
Alumina carrier	Flat mountingslot			AS-NTT0606A-1000	280	0.052	14.56	15.56	1180*125*115	Size : L1000*W7.9*H6.7mm
Aluminium clip	Flat mountingclip			AS-NTT0606S-18	800	0.0011	0.88	1.03	250*250*150	Size : L18*W7.1*H6.7mm with screws
End cap set	End cap set, including end cap and plug (outlet from the bottom direction)			AS-NTT0606GH0-EC	800	0.0009	0.72	1.02	250*250*150	/
Glue	588G acidic glue		/	AS-PG-0002	150	0.014	2.1	2.4	250*250*150	10ml/pcs
Wire	2P PVCWire(0.5m)		/	AS-WS-0019	200	0.0077	1.54	1.84	250*250*150	Suitable for white light strip
Wire	2P PVCWire(2m)			AS-WS-0020	100	0.031	3.1	3.4	250*250*150	
Connector	2PIN IP68 waterproof connector		/	AS-FC-0001	512	0.016	8.192	9.5	365*365*190	Suitable for white light strip


【Solution Of Control System】

Product Image	Product Name	Product number	Order code	Product specifications	Applicable Products
	Monochrome remote	CK1-GBA	402-02-000000-00001	output signal : RF(2.4GHz) Working voltage : 3VDC(CR2032) Remote control distance : 30m Working temperature : Ta:0-30 °C~0+55 °C	Monochrome light strip (Use with CR1-GBA)
	Monochrome light controller	CR1-GBA	402-01-000000-00001	Input voltage : 12-48VDC Output current : 15A@12/24V-10A@36/48V Output Power : 180W@12V-360W@24V 360W@36V-480W@48V Working temperature : Ta:0-30 °C~0+55 °C	Monochrome light strip (Use with CK1-GBA)

【Packaging Solutions】

· Standard Packaging

1. Line marking, the line marking is affixed at a distance of 80mm from the end of the line;



Voltage & bending warningsigns




2. Put the product information label on the back back of the static bag inside the marking line;



Product Information Label



3. Put the light strip into an electrostatic bag, one roll per bag, and seal the bag;



4. Put the product information label and the box number label on the side of the carton, and the QC inspection stamp



ProductInformationLabel

Boxnumberlabel




Model	Size	Product Quantity (box)	Product Quantity (case)	Net weight (kg)	Net weight per box (kg)	Gross weight (kg)	Carton size(m)
NTT0606-9XX12CSN050CCXXX	L5000*6*6mm	5M*6	120M	0.25	6	7.7	0.41*0.41*0.26
NTT0606-9XX24CSN050CCXXX	L5000*6*6mm	5M*6	120M	0.25	6	7.7	

【Reliability Test】

Test Item	Classification	Reference	Test method or condition
Safety test	Mechanical strength	IEC 60598-1 ; IEC 60598-2-21	The hammer spring Impact energy 0.35J
	IP	IEC 60598-1 ; IEC 60598-2-21	IP65
	Winding Test	IEC 60598-1 ; IEC 60598-2-21	φ150mm cylinder, 60N pull, winding 10 times at (-25°C ±2°C) , and 10 times after(-15°C±2°C, 16h).
	Cold Bend Test	IEC 60598-1 ; IEC 60598-2-21	wound on mandrel, low-temperature (-15°C±2°C, 16h) , around the mandrel for two turns
	Cold Impact test	IEC 60598-1 ; IEC 60598-2-21	Low-temperature (-15°C±5°C, 16h), hammer falls from a height of 100mm.
	Insulation Resistance	IEC 60598-1 ; IEC 60598-2-21	≧ 2MΩ
	Electrical strength	IEC 60598-1 ; IEC 60598-2-21	500V
Mechanical reliability testing	Bending test	Colors	Each 200mm , bending up and down 100 times
	Bending test	Colors	Each 200mm, bending left and right 100 times
	Torsion test	Colors	Twist clockwise 5 times and then release, repeat 200 times
	Disassembly and assembly test	Colors	Repeat disassembly and assembly, 10 times
Environment Reliability testing	High temperature storing test	IEC 60068-2-2	80°C, 168h
	Low temperature storing test	IEC 60068-2-1	-40°C, 168h
	High temperature and Humidity impact	IEC 60068-2-78	60°C, 85%RH
	Salt Spray test	IEC 60068-2-11	5% salt solution concentration, 24h
	IK	IEC 62262	5 times of impact on each exposed surface
	Lifetime aging test	Colors	35°C, 6000h
	switch test	Colors	10s On, 10s Off, 10000 times

【Precautions】

- Use a 24V DC isolated power supply to drive the neon lamp strip and the ripple wave of constant voltage source shall be less than 5%. It is not allowed to use RC voltage reduction or non-isolated power supply to drive the neon lamp strip.
- In actual applications, 20% of the power supply shall be kept (only 80% of the power is used) to guarantee that sufficient voltage is available to drive the product.
- Attention shall be paid to safe operation. After powering on, it is not allowed to touch the AC power supply to avoid an electric shock.
- Attention shall be paid to the positive and negative poles of the wires during installation and whether the power supply conforms to required voltages to avoid damages.
- Avoid scratching, distortion and irregular bending of the product during installation; otherwise it may cause irreparable damage to the product.
- Please do not bend the strip into an arc with a diameter less than 30mm to ensure the longevity and reliability, the bending diameter too small will damage the product itself.
- If the actual length of application exceeds the specified using length, it will lead to overload heating and uneven brightness.
- To keep the eyes from being harmed, try to avoid staring at the glowing side of the LED strip for a long time.
- Non-professionals are prohibited from installing, disassembling and repairing the product.
- Do not use any acid or alkaline adhesive to fix products (including not limited to glass cement, etc.)
- Products with different IP grade should be used in different environments, the product with IP65 is not suitable for use in water-immersed environment .
- The final color of products with different sizes and specifications is slightly deviated due to structural differences under the same color temperature, which should be confirmed before use.
- Please use professional cutting tools when cutting.



Top bending error bending ❌



No stretching



No trampling